



Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0

Product name

ACRYLINE AIR DRY PROMOTER SB

(ATH 313)



PRODUCT DESCRIPTION

It is an additive with properties to speed up the curing of 2K products.

INTENDED USES

- it will reduce both bake and air drying times.

FEATURES AND BENEFITS

- It has been designed for small repairs and single panel repairs.

PRODUCT INFORMATION

| | |
|-------------|--------------|
| Appearance | Clear liquid |
| Flash Point | 23°C |

APPLICATION DETAILS

| | |
|--------------|-----------------------------|
| Mixing Ratio | 2.5 % to ready to spray mix |
|--------------|-----------------------------|

| | |
|--------|---|
| Mixing | Stir both components separately with a power mixer until homogenous. Add the curing agent to the base and mix thoroughly together. Mix only in proportions shown above. Then add accelerator. |
|--------|---|

STORAGE AND PACKAGING

Store away from direct sun, heat, open flames, sparks and severe cold.

Shelf Life: 24 months

Dual Packs: 1L



APPLICATION INFORMATION

- Use air fed respirator during application
- For professional use only.
- This product is not designed for full repairs when using a 2 Pack Fast Hardener.
- Use for spot repairs and single panel repairs.
- It will significantly reduce the pot life of the ready to spray

SAFETY PRECAUTIONS

- Always keep paint out of reach of children.
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.
- Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Do not smoke while painting.
- Flammable. Store in a cool dry place away from heat and sparks.
- CATALYST contains isocyanate – use suitable respirator, particularly during spray application of the mixed material.
- Refer to Safety Data Sheet for complete information.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be dependable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging, and colour.



ACRYLINE AIR DRY PROMOTER SB

(ATH 313)

Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,

Factoria, Krugersdorp

South Africa

1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za