

## ACRYLINE PU ACRYLC (APU RANGE)

### SECTION 1. Identification

**GHS product identifier** : Acryline PU Acrylic (APU Range)

**Other means of identification** : Acryline 2K Toner

**Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** : Used for gloss adjustment of Acryline Automotive Top Coats.

**Supplier's details** : Kansai Plascon (Pty) Ltd  
PO Box 1594  
Port Elizabeth  
6000

**Emergency phone** : 041 401 1400 (within hours of operation)

**Facsimile** : 041 453 4596

**National Contact Person** : Mr B. Bhugwandin

### SECTION 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUID - Category 2  
ORGANIC PEROXIDE - Type C  
SERIOUS EYE DAMAGE/ IRRITATION - Category 2  
SKIN CORROSION/ IRRITATION - Category 2  
SKIN SENSITIZATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE - Category 3  
SPECIFIC TARGET ORGAN TOXICITY REPEATED EXPOSURE - Category 2  
ASPIRATION HAZARD - Category 1  
ACUTE TOXICITY (DERMAL) - Category 4  
ACUTE TOXICITY (INHALATION) - Category 4  
AQUATIC TOXICITY (ACUTE) - Category 1  
AQUATIC TOXICITY (CHRONIC) - Category 2

**Label elements according to** : SANS 10234: 2008

**Hazard pictograms** : 

**Signal word** : Danger

**Hazard statements** : H225 - Highly flammable liquid and vapour.  
H242 - Heating may cause fire.  
H304 - May be fatal if swallowed and enters airways.  
H312 - Harmful if in contact with skin.  
H315 - Causes skin irritation.

## ACRYLINE PU ACRYLC (APU RANGE)

---

H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H400 - Very toxic to aquatic life.  
H411 - Toxic to aquatic life with long lasting effects.

### Precautionary statements

General : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read label before use.

Prevention : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P240 - Ground and bond container and receiving equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapor.  
P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P262 - Do not get in eyes, on skin, or on clothing.  
P263 - Wash contaminated clothing before reuse .  
P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves,protective clothing,eye protection or face protection.  
P284 - In case of inadequate ventilation wear respiratory protection.

Response : P312 - Call a POISON CENTER or physician if you feel unwell.  
P314 - Get medical advice or attention if you feel unwell.  
P362 - Take off contaminated clothing and wash before reuse.  
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or physician.  
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+361+353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.  
P304+340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.



## ACRYLINE PU ACRYLC (APU RANGE)

P337+313 - If eye irritation persists get medical advice/attention.  
 P370+380 - In case of fire: Evacuate area.

Storage : P410 - Protect from sunlight.  
 P402+404 - Store in a dry place. Store in a closed container.  
 P403+235 - Store in a well ventilated place. Keep cool.

Disposal : P501 - Dispose of contents/containers in accordance with local regulation.

Other hazards which do not result in classification : None identified.

### SECTION 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Acryline 2K Toner

#### CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	CAS number	%	SANS 10234 Classification
Xylene	1330-20-7	25.0-30.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
n-butyl acetate	123-86-4	25.0-30.0	Flam. Liq. 3, H226 STOT SE 3, H336
Styrene	100-42-5	10.0-15.0	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400
Butyl Methacrylate Monomer	97-88-1	10.0-15.0	Flam.Liq.3, H226 Skin.Irrit.2, H315 Eye.Irrit.2, H319 Skin.Sens.1, H317 STOT-SE.3, H335
2-Hydroxyethyl methacrylate	868-77-9	10.0-15.0	Skin.Irrit.2, H315 Eye.Irrit.2, H319 Skin.Sens.1, H317
Methyl Methacrylate Monomer	80-62-6	5.0-10.0	Flam. Liq. 2, H225 Skin.Irrit.2, H315 Skin.Sens.1, H317 STOT-SE 3, H335
Ethyl benzene	100-41-4	2.0-5.0	Flam.Liq.2, H225 Acute.Tox.4, H332



## ACRYLINE PU ACRYLC (APU RANGE)

			STOT-RE.2, H373 Asp.Haz.1,H304
2-methoxy-1-methylethyl acetate	108-65-6	2.0 - 5.0	Flam. Liq. 3, H226
Tert-butyl perbenzoate	614-45-9	<2.00	Organic. Pero.C, H242 Acute.Tox.4, H332 Skin.Irrit.2, H315 Skin.Sens.1, H317 Aquatic Acute1, H400
Ethylene glycol butyl ether acetate	112-07-2	<2.00	Acute Tox. 4, H312 Acute Tox. 4, H332

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation persist.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Remove contaminated clothing and shoes. Wash contaminated skin with soap or a recognised skin cleaner and plenty of water. Continue to rinse for at least 10 minutes. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



## ACRYLINE PU ACRYLC (APU RANGE)

### Most important symptoms/ effects, acute and delayed

#### Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled. May cause drowsiness or dizziness.
Skin contact	: Harmful in contact with skin. Causes skin irritation.
Ingestion	: May be fatal if swallowed and enters airways.

#### Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include pain or irritation, watering or redness.
Inhalation	: Adverse symptoms may include nausea or vomiting, headache.
Skin contact	: Adverse symptoms may include irritation or redness.
Ingestion	: Adverse symptoms may include nausea or vomiting, headache

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### See toxicological information (Section 11)

## SECTION 5. Fire-fighting measures

### Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire such as dry powder, CO<sub>2</sub>, water spray (fog) or foam. Use fog to cool and control.

Unsuitable extinguishing media : Do not use water jet.

### Specific hazards arising from from the chemical

: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

### Hazardous thermal decomposition products

: Decomposition products may include the following materials  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the



## ACRYLINE PU ACRYLC (APU RANGE)

incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

### Special protective

**equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.



## ACRYLINE PU ACRYLC (APU RANGE)

### SECTION 7. Handling and storage

#### Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

#### Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

### SECTION 8. Exposure controls/personal protection

#### Occupational exposure limits

Ingredient name	Exposure limits
Xylene	<b>OHSA:</b> TWA: OEL-RL 100 ppm; 435 mg/m <sup>3</sup> STEL: OEL-RL 150 ppm; 650 mg/m <sup>3</sup>
n-butyl acetate	<b>OHSA:</b> TWA: OEL-RL 200 ppm; 950 mg/m <sup>3</sup> STEL: OEL-RL 250 ppm; 1190 mg/m <sup>3</sup>
Styrene	<b>OHSA:</b> TWA: OEL-RL 50 ppm; 213 mg/m <sup>3</sup> STEL: OEL-RL 100 ppm; 426 mg/m <sup>3</sup>
Methyl Methacrylate Monomer	<b>OHSA:</b> TWA: OEL-RL 50 ppm; 208mg/m <sup>3</sup> STEL: OEL-RL 100 ppm; 416 mg/m <sup>3</sup>
Ethyl benzene	<b>OHSA:</b> TWA: OEL-RL 100 ppm; 435 mg/m <sup>3</sup> STEL: OEL-RL 125 ppm; 545 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate	<b>WEL:</b>





## ACRYLINE PU ACRYLC (APU RANGE)

Ingredient name	Exposure limits
	STEL: 100 ppm; 548 mg/m <sup>3</sup> LTEL: 50 ppm; 274 mg/m <sup>3</sup>
Ethylene glycol butyl ether acetate	<b>ACGIH (USA):</b> STEL 20 ppm

### Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

#### Hand protection

: Avoid direct contact. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.





## ACRYLINE PU ACRYLC (APU RANGE)

Other skin protection	: Avoid direct contact. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### SECTION 9. Physical and chemical properties

Physical state	: Liquid
Colour	: Yellow (APU 1); Silver (APU 2); Silver (APU 4); Blue (APU 5); Blue (APU 6); Green (APU 7); Red (APU 8); Yellow (APU 9); Clear (APU 10); Red (APU 11); Scarlet (APU 12); Yellow (APU 13); Yellow (APU 14); Black (APU 15); Red (APU 16); Maroon (APU 19); Black (APU 20); Blue (APU 26); Green (APU 27); Red (APU 28); Yellow (APU 29); Red (APU 30); Blue (APU 32); White (APU 35); Green (APU 36); Violet (APU 37); Black (APU 318); Grey (APU 320); White (APU 797582); Orange (APU 797848); Black (APU 798096); Grey (APU 799623).
Odor	: Pungent
Odor threshold	: No data available
pH	: Not applicable
Melting point	: Not applicable
Boiling point	: >35°C
Flash point	: 23°C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Lower and upper explosive (flammable) limits	: No data available
Vapor pressure	: No data available
Vapor density	: No data available
Relative density	: 0.947 – 1.40
Solubility	: Soluble in organic solvents, insoluble in water



## ACRYLINE PU ACRYLC (APU RANGE)

Partition coefficient, n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	: 85 - 90 sec D4 @20°C 75 - 80 sec D4 @20°C (APU 10) 80 - 85 sec D4 @20°C (APU 26; APU 27; APU 28; APU 29; APU 30; APU 35; APU 36)

### SECTION 10. Stability and reactivity

<b>Reactivity</b>	: Inert - no reaction with fire-fighting water.
<b>Chemical stability</b>	: Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	: Any reactive substances – oxidisers in particular.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11. Toxicological information

#### Acute Toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Xylene	LD50 Dermal	Rabbit	<2000 mg/kg	-
	LC50 Inhalation	Rat	<10.0 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
n-butyl acetate	LD50 Dermal	Rabbit	>14.112 mg/kg	-
	LC50 Inhalation	Rat	>21 mg/l	4 hours
	LD50 Oral	Rat	10760 mg/kg	-
Styrene	LD50 Oral	Rat	316 mg/kg	4 hours
	LC50 Inhalation Gas	Rat	9500 ppm	4 hours
Butyl Methacrylate Monomer	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LC50 Inhalation	Rat	29 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
Methyl Methacrylate Monomer	LC50 Inhalation Gas	Rat	29.8 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-



**ACRYLINE PU ACRYLC (APU RANGE)**

Product/ingredient name	Result	Species	Dose	Exposure
	LD50 Dermal	Rabbit	>5000 mg/kg	-
Ethyl benzene	LD50 Dermal LD50 Oral	Rabbit Rat	15.433 mg/kg 3500 mg/kg	- -
2-Methoxy-1-methylethyl acetate	LD50 Oral LD50 Oral LD50 Dermal LC50 Inhalation	Rat, male Rat, female Rabbit Rat	>10,000 mg/kg 8,532 mg/kg >5,000 mg/kg > 4,345 ppm	- - - 6 hours
Tert-butyl perbenzoate	LD50 Dermal LC50 Inhalation LD50 Oral	Rabbit Rat Rat	>2000 mg/kg 1.01 mg/l 2000 mg	- 4 hours -
Ethylene glycol butyl ether acetate	LD50 Oral LD50 Dermal	Rat Rabbit	7250 mg/kg 1540 mg/kg	- -

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Eyes - Irritation Skin - Irritation	Rabbit Rabbit	- -	87 mg 100 %	Mild irritant Moderate irritant
n-butyl Acetate	Skin - Irritant Eyes - Irritant	Rabbit Rabbit	- -	4 hours -	No irritation No irritation
Styrene	Eyes - Irritation Skin - Irritation Inhalation -Irritation	- - -	- - -	- - -	Moderate irritant Moderate irritant Moderate irritant
Butyl Methacrylate Monomer	Skin - Irritation Skin - Irritation Skin - Sensitization	Rabbit Guinea pigs -	- - -	4 hours 4w,6h/d,5 4w,6h/d,5	Slightly irritant Slightly irritant Sensitizer
Methyl Methacrylate Monomer	Eyes - Irritation Skin - Irritation Inhalation -Irritation	Rabbit Guinea pigs -	- - -	- - -	Slightly irritant Moderate irritant Moderate irritant
Tert-butyl perbenzoate	Skin - Irritation Skin - Sensitization	- -	- -	- -	Slightly irritant Sensitizer
Ethyl benzene	Eyes - Irritation Skin - Irritation	Rabbit Rabbit	- -	- -	Mild irritant Moderate irritant

**Specific target organ toxicity (single exposure)**

Name	Category	Route of exposure	Target Organs
n-butyl Acetate	Category 3	Not determined	Not determined
Butyl Methacrylate Monomer	Category 3	Not determined	Not determined
Methyl Methacrylate Monomer	Category 3	Not determined	Not determined

**Specific target organ toxicity (repeated exposure)**

Name	Category	Route of exposure	Target Organs
ethyl benzene	Category 2	Not determined	Not determined

## ACRYLINE PU ACRYLC (APU RANGE)

### Aspiration hazard

Name	Result
ethyl benzene	ASPIRATION HAZARD

Information on the likely routes of exposure : Inhalation, skin and eye contact.

### Potential acute health effects

Eye contact : Causes serious eye irritation.  
 Inhalation : Harmful if inhaled. May cause drowsiness or dizziness.  
 Skin contact : Harmful in contact with skin. Causes skin irritation.  
 Ingestion : May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include pain or irritation, watering or redness.  
 Inhalation : Adverse symptoms may include nausea or vomiting, headache.  
 Skin contact : Adverse symptoms may include irritation or redness.  
 Ingestion : Adverse symptoms may include nausea or vomiting, headache

### Potential Chronic health effects

General : May cause damage to organs through prolonged or repeated exposure.  
 Carcinogenicity : No known significant effects or critical hazards  
 Mutagenicity : No known significant effects or critical hazards  
 Teratogenicity : No known significant effects or critical hazards  
 Developmental effects : No known significant effects or critical hazards.  
 Fertility effects : No known significant effects or critical hazards

### Acute toxicity estimates

No data available.

## SECTION 12. Ecological information

### Toxicity

Product/Ingredient name	Result	Species	Exposure
Xylene	Acute LC50 8500ug/l	Aquatic - Crustaceans Palaemonetes	48 hours
	Acute LC50 3300 to 4093ug/l	Fish - Pugio Oncorhynchus mykiss	96 hours
n-butyl Acetate	Acute LC50 18 mg/l	Fish - Pimephales promelas	96 hours
	Acute EC50 44 mg/l	Organic - Daphnia magna	48 hours
	Acute EC50 674,7 mg/l	Algae - Desmodesmus subspicatus	72 hours
Butyl Methacrylate Monomer	Acute LC50 5.57 mg/l	Fish - Oryzias lapites	96 hours
	Acute LC50 1.67 mg/l	Fish - Oryzias lapites	14 days
	Acute EC50 25.4 mg/l	Organic - Daphnia magna	48 hours
	Acute EC50 1.1 mg/l	Organic - Daphnia magna	21 days
	Acute EC50 24.8 mg/l	Algae - Skeletonema costatum	72 hours
	Acute EC50 253.6 mg/l	Bacteria - Pseudomonas putida	10 hours
Methyl Methacrylate Monomer	Acute LC50 > 100 mg/l	Fish - Oncorhynchus mykiss	-
	Acute LC50 130 mg/l	Fish - Fathead minnow	96 hours

**ACRYLINE PU ACRYLC (APU RANGE)**

	Acute EC50 69 mg/l Acute EC50 170 mg/l NOEC 8.4mg/l Algae	Aquatic - Daphnia magna Algae - Skeletonema costatum Algae - Zebra fish	48 hours 96 hours 35 days
Ethyl benzene	Acute LC50 4.2 mg/l Acute EC50 1.8-2.4 mg/l Acute EC50 4.9 mg/l	Fish - Oncorhynchus mykiss Aquatic - Daphnia magna Algae - Skeletonema costatum	96 hours 48 hours 72 hours
2-Methoxy-1-methylethyl acetate	Acute LC50, 100 - 180 mg/l Acute LC50, 408 - 500 mg/l	Fish - rainbow trout Aquatic - Daphnia magna	- -
Ethylene glycol butyl ether acetate	Acute LC50, 140 mg/l Acute EC50, 37 – 180 mg/l Acute EC50, > 500 mg/l Acute LC50, 22 - 31 mg/l Acute LC50, 80 mg/l Fish	Aquatic - Daphnia magna Aquatic - Daphnia magna Algae - Scenedesmus subspicatus Fish - Pimephales promelas Fish - Leuciscus idus	- - - -
Tert-butyl perbenzoate	Acute LC50 1.6 mg/l Fish Acute LC50 11 mg/l Acute EC50 0.8 mg/l Acute EC50 43 mg/l	Fish - Zebrafish Aquatic - Daphnia magna Algae - Scenedesmus subspicatus Bacteria	96 hours 24 hours 72 hours 30 minutes

**Persistence and degradability**

Product/Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Xylene	Fresh water <28 days	1 to 2 day(s)	-
n-Butyl Acetate	Exposure time 28 days	-	83 % Readily biodegradable
Butyl Methacrylate Monomer	-	-	Readily
Methyl Methacrylate Monomer	-	-	Readily
ethyl benzene	-	-	70-80% Readily
Tert-butyl perbenzoate	-	-	Readily

**Bioaccumulative potential**

Product/Ingredient name	LogPow	BCF	Potential
Xylene	3.12	20	Low
Methyl Methacrylate Monomer	-	-	Low
Ethylene glycol butyl ether acetate	<3.0	<100	Low

**Mobility in soil**

Soil/ water partition coefficient

 (K<sub>oc</sub>) : No data available.

Mobility : No data available.

**PBT/vPvB data** : P: No data available. B: No data available. T: No data available.

**Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13. Disposal considerations**




Disposal methods : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via



## ACRYLINE PU ACRYLC (APU RANGE)

the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### SECTION 14. Transport information

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air - IATA
UN number	1263	1263	1263
UN proper shipping name	Paint related material	Paint related material	Paint related material
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	Environmentally hazardous	Marine pollutant	Environmentally hazardous
Additional information	No data available	Emergency schedules (EmS) F-E, S-E	<b>Passenger and Cargo Aircraft Ltd QTY:</b> Quantity limitation: 10 L Packaging instructions: Y344 <b>Passenger and Cargo Aircraft:</b> Quantity limitation: 60 L Packaging instructions: 355 <b>Cargo Aircraft Only:</b> Quantity limitation: 220 L Packaging instructions: 366

## ACRYLINE PU ACRYLC (APU RANGE)

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air - IATA
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available	No data available	No data available

### SECTION 15. Regulatory information

#### Safety, health and environmental regulations specific for the product

**Relevant information regarding authorization:** Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances.

**Relevant information regarding restrictions:** None known.

**EU regulations:** Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC

**Other National regulations:** None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166- European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

### SECTION 16. Other information

#### History

Date of printing : 19/06/2019

Date of previous issue : 25/10/2017

#### Key to abbreviations

: ATE = Acute Toxicity Estimate

BCP Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogP<sub>ow</sub> = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OHSA = Occupational Health and Safety Act, 1993 (South Africa)

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

UN = United Nations





## ACRYLINE PU ACRYLC (APU RANGE)

---

**References** : Supplier safety data sheets.

**Further information:**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

**Notice to readers:**

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

**Legal disclaimer:**

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

