

MASTERMIX 2K ACCELERATOR (PTK 313)**SECTION 1. Identification****GHS product identifier** : Mastermix 2K Accelerator (PTK 313)**Other means of identification** : PTK 313**Relevant identified uses of the substance or mixture and uses advised against****Identified uses** : A paint or paint constituent product.**Supplier's details** : Kansai Plascon (Pty) Ltd
P.O. Box 1594
Port Elizabeth
6000**Emergency phone** : (041) 401 1400 (within hours of operation)**Facsimile** : (041) 453 4596**National Contact Person** : Mr B. Bhugwandin**SECTION 2. Hazards identification****Classification of the substance or mixture** : FLAMMABLE LIQUID - Category 2
SERIOUS EYE DAMAGE/ IRRITATION - Category 2
SKIN CORROSION/ IRRITATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE - Category 3
SPECIFIC TARGET ORGAN TOXICITY REPEATED EXPOSURE - Category 2
ASPIRATION HAZARD - Category 1
ACUTE TOXICITY (DERMAL) - Category 4
ACUTE TOXICITY (ORAL) - Category 4
ACUTE TOXICITY (INHALATION) - Category 4**Label elements according to** : SANS 10234: 2008**Hazard pictograms** : **Signal word** : Danger**Hazard statements** : H225 - Highly flammable liquid and vapour.
H302 - Harmful if swallowed.
H304 - May be fatal if swallowed and enters airways.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H336 - May cause drowsiness or dizziness.

MASTERMIX 2K ACCELERATOR (PTK 313)

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

General : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Prevention : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 - Ground and bond container and receiving equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapor.
P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray.
P262 - Do not get in eyes, on skin, or on clothing.
P263 - Wash contaminated clothing before reuse .
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves,protective clothing,eye protection or face protection.
P284 - In case of inadequate ventilation wear respiratory protection.

Response : P312 - Call a POISON CENTER or physician if you feel unwell.
P314 - Get medical advice or attention if you feel unwell.
P362 - Take off contaminated clothing and wash before reuse.
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or physician.
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.
P304+340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P337+313 - If eye irritation persists get medical advice/attention.
P370+380 - In case of fire: Evacuate area.

Storage : P410 - Protect from sunlight.
P402+404 - Store in a dry place. Store in a closed container.
P403+235 - Store in a well ventilated place. Keep cool.

Disposal : P501 - Dispose of contents/containers in accordance with local regulation.



MASTERMIX 2K ACCELERATOR (PTK 313)

Other hazards which do not
Result in classification : None identified.

SECTION 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : PTK 313

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	CAS number	%	SANS 10234 Classification
n-butyl acetate	123-86-4	65.0-70.0	Flam. Liq. 3, H226 STOT-SE. 3, H336
Ethylene glycol butyl ether	111-76-2	5.0-10.0	Acute Tox. 4, H302 Acute Tox 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Xylene	1330-20-7	5.0-10.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315
Methyl ethyl ketone	78-93-3	5.0-10.0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Skin Irrit. 2, H315 STOT SE 3, H336
Ethyl acetate	141-78-6	2.0-5.0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Ethyl Benzene	100-41-4	<2.0	Flam.Liq.2, H225 Acute.Tox.4, H332 STOT-RE.2, H373 Asp.Haz.1,H304

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

SECTION 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation persist.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for



MASTERMIX 2K ACCELERATOR (PTK 313)

breathing. Get medical attention if symptoms occur.

Skin contact : Remove contaminated clothing and shoes. Wash contaminated skin with soap or a recognised skin cleaner and plenty of water. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/ effects, acute and delayedPotential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : Harmful if inhaled. May cause drowsiness or dizziness.
Skin contact : Harmful in contact with skin. Causes skin irritation.
Ingestion : Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include pain or irritation, watering or redness.
Inhalation : Adverse symptoms may include nausea or vomiting, headache, drowsiness fatigue or dizziness.
Skin contact : Adverse symptoms may include irritation or redness.
Ingestion : May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments : No specific treatment.
Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

SECTION 5. Fire-fighting measures

MASTERMIX 2K ACCELERATOR (PTK 313)

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire such as dry powder, CO₂, water spray (fog) or foam. Use fog to cool and control.

Unsuitable extinguishing media : Do not use water jet.

**Specific hazards arising from
from the chemical**

: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal
decomposition products**

: Decomposition products may include the following materials
carbon dioxide
carbon monoxide
metal oxide/oxides

**Special protective actions
for fire-fighters**

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective
equipment for fire-fighters**

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

For non-emergency
personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).



MASTERMIX 2K ACCELERATOR (PTK 313)**Methods and materials for containment and cleaning up**

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. Handling and storage**Precautions for safe handling**

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

Conditions for safe storage,

including any incompatibilities : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

SECTION 8. Exposure controls/personal protection

Occupational exposure limits



MASTERMIX 2K ACCELERATOR (PTK 313)

Ingredient name	Exposure limits
n-butyl acetate	OHSA: TWA: OEL-RL 200 ppm; 950 mg/m ³ STEL: OEL-RL 250 ppm; 1190 mg/m ³
Ethylene glycol butyl ether	ACGIH TLV: STEL: 25 ppm; 120 mg/m ³
Xylene	OHSA: TWA: OEL-RL 100 ppm; 435 mg/m ³ STEL: OEL-RL 150 ppm; 650 mg/m ³
Methyl ethyl ketone	ACGIH TLV (USA): TWA: OEL-RL: 200 ppm; 590 mg/m ³ STEL: OEL-RL: 300 ppm; 885 mg/m ³
Ethyl acetate	WEL: STEL: 400 ppm LTEL: 200 ppm
Ethyl Benzene	OHSA: TWA: OEL-RL 100 ppm; 435 mg/m ³ STEL: OEL-RL 125 ppm; 545 mg/m ³

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



MASTERMIX 2K ACCELERATOR (PTK 313)

Eye/face protection	: Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary e.g. in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9. Physical and chemical properties

Physical state	: Liquid
Colour	: Clear
Odour	: No data available
Odor threshold	: No data available
pH	: Not applicable
Melting point	: Not applicable
Boiling point	: 127 °C
Flash point	: 23°C
Evaporation rate	: No data available
Flammability (solid, gas) Lower and upper explosive (flammable) limits	: No data available

MASTERMIX 2K ACCELERATOR (PTK 313)

Vapor pressure	: No data available
Vapor density	: No data available
Relative density	: 0.851 – 0.891
Solubility	: Soluble in organic solvents
Partition coefficient, n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity (Ford 4 Cup)	: No data available

SECTION 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No available data.
Incompatible materials	: No available data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11. Toxicological information

Acute Toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LD50 Dermal	Rabbit	>14.112 mg/kg	-
	LC50 Inhalation	Rat	>21 mg/l	4 hours
	LD50 Oral	Rat	10760 mg/kg	-
Ethylene glycol butyl ether	LD50 Oral	Rat	470 mg/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LC50 Inhalation	Rat	450 ppm	4 hours



MASTERMIX 2K ACCELERATOR (PTK 313)

Product/ingredient name	Result	Species	Dose	Exposure
Xylene	LD50 Dermal	Rabbit	<2000 mg/kg	-
	LC50 Inhalation	Rat	<10.0 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
Methyl ethyl ketone	LD50 Oral	Rat	2737 mg/kg	-
	LD50 Dermal	Rabbit	13000 mg/kg	-
	LC50 Inhalation (vapour)	Rat	13500 mg/m ³	8 hours
Ethyl acetate	LD50 Oral	Rat	5620 mg/kg	-
	LD50 Oral	Rabbit	4940 mg/kg	-
	LC50 Inhalation	Rabbit	2500 mg/l	4 hours
	LC50 Inhalation	Rat	4000 mg/l	4 hours
Ethyl Benzene	LD50 Dermal	Rabbit	15.433 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Skin - Irritation	Rabbit	-	4 hours	Not irritant
	Eye - Irritation	Rabbit	-	-	Not irritant
Xylene	Skin - Irritation	Rabbit	-	87 mg	Mild irritant
	Eyes - Irritation	Rabbit	-	100 %	Moderate irritant
Ethyl Benzene	Skin - Irritation	Rabbit	-	24 hours	Mild irritant
	Eyes - Irritation	Rabbit	-	-	Moderate irritant

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target Organs
n-butyl acetate	Category 3	Not determined	Not determined
Methyl ethyl ketone	Category 3	Not determined	Not determined
Ethyl acetate	Category 3	Not determined	Not determined

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target Organs
Ethyl Benzene	Category 2	Inhalation	Liver or Kidney

Aspiration hazard

Name	Result
Ethyl Benzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Inhalation, skin and eye contact.

Potential acute health effects

Eye contact : Causes serious eye irritation.
 Inhalation : Harmful if inhaled. May cause drowsiness or dizziness.
 Skin contact : Harmful in contact with skin. Causes skin irritation.
 Ingestion : Harmful if swallowed.

MASTERMIX 2K ACCELERATOR (PTK 313)
Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include pain or irritation, watering or redness.
 Inhalation : Adverse symptoms may include nausea or vomiting, headache, drowsiness fatigue or dizziness.
 Skin contact : Adverse symptoms may include irritation or redness.
 Ingestion : May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure.

Potential Chronic health effects

General : May cause damage to organs through prolonged or repeated exposure.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards

Acute toxicity estimates

No data available

SECTION 12. Ecological information
Toxicity

Product/Ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 18 mg/l Acute EC50 44 mg/l Acute EC50 674,7 mg/l	Fish - Pimephales promelas Organic - Daphnia magna Algae - Desmodesmus	96 hours 48 hours 72 hours
Ethylene glycol butyl ether	Acute LC50 1474 mg/l Acute EC50 1550 mg/l Acute EC50 1840 mg/l	Fish - Rainbow Trout Aquatic - Daphnia magna Algae – Green algae	96 hours 48 hours 72 hours
Xylene	Acute LC/EC50 8.05 mg/l Acute LC/EC50 >1 mg/l Acute LC/EC50 >45 mg/l	Fish - Rainbow trout Aquatic - Daphnia magna Algae - Green algae	96 hours 48 hours 3 hours
Methyl ethyl ketone	Acute LC50 5640 mg/l Acute LC50 1950 mg/l Acute EC50 10000-20000 ppm Acute EC50 100-10000 ppm Acute EC50 3000-10000 mg/l	Fish - Bluegill sunfish B Aquatic - rine shrimp ASRI Test Growth Inhibition Test Algal growth Inhibition test	24 hours 24 hours - - -
Ethyl acetate	Acute LC50 230 mg/l	Fish - Pimephales promelas	96 hours
Ethyl Benzene	Acute LC50 4.2 mg/l Acute EC50 1.8-2.4 mg/l Acute EC50 4.9 mg/l	Fish - Oncorhynchus mykiss Aquatic - Daphnia magna Algae - Skeletonema costatum	96 hours 48 hours 72 hours

Persistence and degradability

Product/Ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	aerobic - Exposure time 28 days	-	83 % Readily
Ethylene glycol butyl ether	aerobic - Exposure time 28 days	-	90.4% Readily
Xylene	Fresh water <28 days	1 to 2 day(s)	-

MASTERMIX 2K ACCELERATOR (PTK 313)

Product/Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Methyl ethyl ketone	BOD5: 1515-1.92 mg/l in 5 days COD: 2.2-2.31 mg/l BOD 6% in 28 days	- - -	Readily
Ethyl Benzene	Fresh water 28 days - 70 – 80%	1 to 2 day(s)	Readily

Bioaccumulative potential

Product/Ingredient name	LogPow	BCF	Potential
Xylene	3.12	20	Low
Methyl ethyl ketone	0.29	-	Low

Mobility in soil

Soil/ water partition coefficient (K_{oc}) : No data available.

Mobility : No data available.

PBT/vPvB data : P: No data available. B: No data available. T: No data available.

Other adverse effects : No known significant effects or critical hazards.

SECTION 13. Disposal considerations




Disposal methods : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. Transport information

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air - IATA
UN number	1263	1263	1263
UN proper shipping name	Paint	Paint	Paint
Transport hazard class(es)	3	3	3



MASTERMIX 2K ACCELERATOR (PTK 313)

			
Packing group	II	II	II
Environmental hazards	No	No	No
Additional information	No data available	Emergency schedules (EmS) F-E, S-E	Passenger and Cargo Aircraft Ltd QTY: Quantity limitation: 1 L Packaging instructions: Y341 Passenger and Cargo Aircraft: Quantity limitation: 5 L Packaging instructions: 353
			Cargo Aircraft Only:
			Quantity limitation: 60 L Packaging instructions: 364
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No data available	No data available	No data available

SECTION 15. Regulatory information

Safety, health and environmental regulations specific for the product

: Relevant information regarding authorization: Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances.

Relevant information regarding restrictions: None known.

EU regulations: Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC

Other National regulations: None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166- European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

SECTION 16. Other information

History



MASTERMIX 2K ACCELERATOR (PTK 313)

Date of printing : 06/12/2019

Date of previous issue : 29/10/2014

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCP Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogP_{ow} = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OHSA = Occupational Health and Safety Act, 1993 (South Africa)

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

UN = United Nations

References

: Supplier safety data sheets.

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to readers:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.