

Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0

Product name

# PLASCOLAC 7300 WB

PIGMENT DISPERSION(LD RANGE)



## PRODUCT DESCRIPTION

A range of water-based pigment dispersions.

## INTENDED USES

- For use as pigment pastes and provides extremely stable pigment dispersion for application in a range of water borne coatings.

## FEATURES AND BENEFITS

- Strength controlled dispersions
- Compatibility with a wide range of water-based coatings.
- Does not affect the performance properties of the tinted products.

## PRODUCT INFORMATION

Colours	Super White(LD 500), Caramel(LD 502), Tan (LD 503), Jet Black(LD 504), Army Shade (LD 506)
Flash Point	Non flammable
Viscosity	90 – 95KU (typical)

## APPLICATION DETAILS

Mixing	Stir with a flat paddle until completely homogeneous then add to paint and stir until homogeneous colour is obtained.
--------	---

## STORAGE AND PACKAGING

Store away from direct sun, heat, open flames, sparks and severe cold.  
Shelf Life: 24 months  
Single Pack: 20L



PLASCOLAC 7300 SB

(LD RANGE)

Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0

## SAFETY PRECAUTIONS

- Always keep paint out of reach of children.
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.
- Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Do not smoke while painting.
- Flammable. Store in a cool dry place away from heat and sparks.
- Refer to Safety Data Sheet for complete information.

## DISCLAIMER

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be dependable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging, and colour.

## KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,  
Factoria, Krugersdorp  
South Africa  
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

**PLASCON ADVISORY SERVICE:** 0860 20 40 60

**EMAIL:** [advice@kansaiplascon.co.za](mailto:advice@kansaiplascon.co.za)