

Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0

Product name

THINNER 5010

PU ACRYLIC THINNER (AW 260)



PRODUCT DESCRIPTION

A solvent blend formulated specifically for thinning polyurethane coatings.

INTENDED USES

- Used to thin products, particularly polyurethanes, prior to application, as specified.
- To clean equipment e.g., paint rollers, brushes etc.

PRODUCT INFORMATION

Appearance	Colourless liquid
Flash Point	9°C(typical)

APPLICATION DETAILS

Mixing Only use in proportion specified. Do not exceed quantity.

STORAGE AND PACKAGING

Store away from direct sun, heat, open flames, sparks and severe cold.

Shelf Life: 24 months

Single Packs: 5L

APPLICATION INFORMATION

Not recommended for thinning enamels since it may cause lifting of the previous coat.

Use as recommended solvent described in individual product datasheets.

SAFETY PRECAUTIONS

- Always keep paint out of reach of children.
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.



THINNER 5010

(AW 260)

Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0

- Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Do not smoke while painting.
- Flammable. Store in a cool dry place away from heat and sparks.
- Refer to Safety Data Sheet for complete information.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be dependable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging, and colour.

KANSAI PLASCON (PTY) LTD

10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.

Tel: +27 11 951 4500

Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60

EMAIL: advice@kansaiplascon.co.za