



Safety Data Sheet

According to UN GHS

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 11.0

Product name

STEELTECT 1400 SB

COASTCOTE ETCH PRIMER (SNK RANGE)



SECTION 1: IDENTIFICATION

GHS product identifier : STEELTECT 1400 SB (SNK RANGE)

Other means of identification : A premium quality range of fast drying, single pack polyvinyl butyral pre-treatment primers.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Pre-treatment primer for mild steel and galvanized iron prior to applying the full paint system. Can be used as a primer/finishing coat in a variety of applications. Ideal for use on vehicle chassis and under body components, engine parts, metal fireplaces, burglar bars, security gates. Wrought iron, etc. For application to abraded aluminum.

Restrictions of use : Do not use in areas / substrates other than specified for in identified uses / TDS.

Supplier's details : Kansai Plascon (Pty) Ltd
P.O. Box 4010
Luipaardsvlei
1743

Emergency phone : +2711 951 4500 (within hours of operation)
Cell phone : +2783 991 5782 (outside hours of operation)
Facsimile : +2711 955 2841
National Contact Person : Misheck Mundondo

SECTION 2: HAZARDOUS IDENTIFICATION

Classification of the substance or mixture

: FLAMMABLE LIQUID - Category 2
 SERIOUS EYE DAMAGE/ IRRITATION - Category 1
 SKIN CORROSION/ IRRITATION - Category 2
 REPRODUCTIVE TOXICITY (Unborn child) - Category 2
 SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE
 - Category 3 ACUTE TOXICITY (ORAL) - Category 4
 ACUTE TOXICITY (INHALATION) - Category 4

Label elements according to

: UN GHS

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 - Highly flammable liquid and vapour.
 H302 - Harmful if swallowed
 H315 - Causes skin irritation.
 H318 - Causes serious eye damage.
 H332 - Harmful if inhaled.
 H335 - May cause respiratory irritation.
 H336 - May cause drowsiness or dizziness.
 H361d - Suspected of damaging the unborn child.

Precautionary statements

General

: P101 - If medical advice is needed, have product container or label at hand.
 P102 - Keep out of reach of children.
 P103 - Read carefully and follow all instructions.

Prevention

: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat/sparks/open flames/hot surfaces.
 - No smoking.
 P240 - Ground and bond container and receiving equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P260 - Do not breathe vapor.

P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray.
P262 - Do not get in eyes, on skin, or on clothing.
P263 - Wash contaminated clothing before reuse.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink, or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection or face protection.
P284 - In case of inadequate ventilation wear respiratory protection.

Response

: P319 - Get medical advice or attention if you feel unwell.
P362 - Take off contaminated clothing and wash before reuse.
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or physician.
P303+361+353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.
P304+340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P337+313 - If eye irritation persists get medical advice/attention.
P370+380 - In case of fire: Evacuate area.

Storage

: P410 - Protect from sunlight.
P402+404 - Store in a dry place. Store in a closed container.
P403+235 - Store in a well-ventilated place. Keep cool.

Disposal

: P501 - Dispose of contents/containers in accordance with local regulation

Other hazards which do not result in classification

: None identified.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Substance/mixture

: Mixture

Other means of identification : A premium quality range of fast drying, single pack polyvinyl butyral pre-treatment primers.

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	CAS number	%	UN GHS Classification
Toluene	108-88-3	40.0-50.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 Acute Tox. 5, H303 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Rep. Tox. 2, H361d
n-butanol (dry basis)	71-36-3	5.0-10.0	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 1, H318 STOT-SE. 3, H335, H336
3-Methyl-2-butanol (Pentanol Isomers)	598-75-4	< 2.00	Flam. Liq. 3, H226 Acute Tox. 4, H332 STOT-SE 3, H335
Iso-butanol	78-83-1	< 2.0	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 1, H318 STOT SE 3, H 335, H336

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: FIRST AID MEASURES

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation persists.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Skin contact : Remove contaminated clothing and shoes. Wash contaminated



skin with soap or a recognised skin cleaner and plenty of water. Avoid the use of solvents. Get medical attention if symptoms persist. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Remove victim to fresh air and keep at rest in a position Comfortable for breathing. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/ effects, acute and delayed**Potential acute health effects****Eye contact**

: Causes serious eye damage.

Inhalation

: Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin contact

: Causes skin irritation.

Ingestion

: Harmful if swallowed.

Over-exposure signs/symptoms**Eye contact**

: Adverse symptoms may include pain or irritation, watering or redness.

Inhalation

: Adverse symptoms may include nausea or vomiting, headache, reduced fetal weight, increase in fetal deaths or skeletal malformations.

Skin contact

: Adverse symptoms may include irritation or redness, reduced fetal weight, increase in fetal deaths or skeletal malformations.

Ingestion

: May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure, reduced fetal weight, increase in fetal deaths or skeletal malformations.

Indication of immediate medical attention and special treatment needed, if necessary**Notes to physician**

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.



Protection of first aiders : No action shall be taken involving any personal risk or without Suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire such as dry powder, CO₂, water spray (fog) or foam. Use fog to cool and control.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials
carbon dioxide
carbon monoxide
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face



piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk-through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non combustible, absorbent material e.g., sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.



SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame, or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool, and well ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits

Ingredient name	Exposure limits
Toluene	OHSA: TWA: OEL-RL 100 ppm; 375 mg/m ³ STEL: OEL-RL 150 ppm; 560 mg/m ³
n-butanol (dry basis)	OHSA: STEL: OEL: RL 50 ppm; 150 mg/m ³
3-Methyl-2-butanol (Pentanol Isomers)	OHSA: TWA: OEL-RL 100 ppm; 360 mg/m ³ STEL: OEL-RL 125 ppm; 450 mg/m ³



Ingredient name	Exposure limits
Iso-butanol	ACGIH (US): TWA: 50 ppm (8 hour(s)); 152 mg/m ³ (8 hour(s)).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is necessary.

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary e.g., in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid
Colour	: White (SNK 1), Red Oxide (SNK 2), Ivory (SNK 5) Matt Black (SNK 10), Blue Grey (SNK 12), Jet Black (SNK 74)
Odour (Threshold)	: No data available
Melting point	: Not applicable
Boiling point	: No data available
Flammability (gas, liquid, solid)	: No data available
Lower and upper explosive (flammable) limits	: No data available
Flash point	: 23°C
Auto-ignition Temperature	: No data available



STEELTECT 1400 SB

(SNK RANGE)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 11.0

Decomposition Temperature	: No data available
pH	: Not applicable
Viscosity	: 40 – 45 seconds (typical)
Solubility	: Soluble in organic solvents, insoluble in water
Partition coefficient, n-octanol/water	: No data available
Evaporation rate	: No data available
Vapour pressure	: No data available
Relative density	: 1.02 g/ml (typical)
Vapour density	: No data available
Particle characteristics	: No data available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Ignition of vapours may lead to explosion. Formation of explosive gas/air mixtures.
Conditions to avoid	: Keep away from heat. Keep away from flames and sparks.
Incompatible materials	: Strong acids and oxidizing agents.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Ingredient name	Result	Species	Dose	Exposure
Toluene	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Rabbit Rat	>7000 mg/kg >2000 mg/kg <20 mg/l	- - 4 hours
n-butanol (dry basis)	LDLo Subcutaneous LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rabbit Rat Rabbit Rat	3 g/kg 24000 mg/m3 3400 mg/kg 790 mg/kg	- 4 hours - -
Iso-butanol	LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rat Rabbit Rat	19200 mg/m3 3400 mg/kg 2460 mg/kg	4 hours - -

Irritation/Corrosion

Ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Skin – Irritation Eyes - Irritation	Rat Rabbit	<3 12 18 18 16 9	24 hours 24 hours 48 hours 72 hours 4 days 7 days	- - - - - -
n-butanol (dry basis)	Eyes - Irritation Skin – Irritation Skin - Irritation	Rabbit Rabbit Rabbit	- - -	24 hrs. 2 mg 0.005 mL 24 hrs. 20 mg	Severe irritant Severe irritant Moderate irritant

Specific target organ toxicity (single exposure)

Ingredient name	Category	Route of exposure	Target Organs
n-butanol (dry basis)	Category 3	Not determined	Respiratory tract irritation and Narcotic effects
3-Methyl-2-butanol (Pentanol Isomers)	Category 3	Not determined	Respiratory tract irritation
Iso-butanol	Category 3	Not determined	Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

Information on the likely routes of exposure

: Inhalation, skin, and eye contact.

Potential acute health effects

Eye contact

: Causes serious eye damage.

Inhalation

: Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Skin contact

: Causes skin irritation.

Ingestion

: Harmful if swallowed

Symptoms related to the physical, chemical, and toxicological characteristics

Eye contact

: Adverse symptoms may include pain or irritation, watering or redness.

Inhalation

: Adverse symptoms may include nausea or vomiting, headache, reduced fetal weight, increase in fetal deaths or skeletal malformations.

Skin contact

: Adverse symptoms may include irritation or redness, reduced fetal weight, increase in fetal deaths or skeletal malformations.

Ingestion

: May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure, reduced fetal weight, increase in fetal deaths or skeletal malformations.

Potential Chronic health effects

General

: No known significant effects or critical hazards.

Carcinogenicity

: No known significant effects or critical hazards.

Mutagenicity

: No known significant effects or critical hazards.

Teratogenicity

: Suspected of damaging fertility or the unborn child.

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: Suspected of damaging fertility or the unborn child.

Acute toxicity estimates

No data available

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ingredient name	Result	Species	Exposure
Toluene	Acute LC50 8.1 mg/l	Fish - Salmon	96 hours
	Acute EC 6.00 mg/l	Aquatic - Daphnia magna	48 hours
	Acute EC50 9.4 mg/l	Algae - Green algae	8 hours
n-butanol (dry basis)	Acute EC50 1983000	Aquatic - Daphnia magna - 6 to 24 hrs.	48 hours
	Acute LC50 100 to 500 mg/L		96 hours



STEELTECT 1400 SB

(SNK RANGE)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 11.0

Ingredient name	Result	Species	Exposure
		Fish - Lepomis macrochirus – 0.1 g	
Iso-butanol	Acute LC50 600000 ug/L Acute LC50 1030000 ug/L Acute LC50 1330000 ug/L Chronic NOEC 4000 ug/L	Crustaceans - Artemia salina – Nauplii Aquatic – Daphnia magna Fish - Oncorhynchus mykiss -1.67g Aquatic - Daphnia magna - 24 hrs.	48 hours 48 hours 96 hours 21 days

Persistence and degradability

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
n-butanol (dry basis)	Fresh water 2 to 29 days	2 days	Readily
Iso-butanol	Fresh water 4 days	< 28 days	-

Bio accumulative potential

Ingredient name	LogPow	BCF	Potential
Toluene	-	<100	-
n-butanol (dry basis)	0.9	3	Low
Iso-butanol	0.8	-	Low

Mobility in soil

Soil/ water partition
coefficient (KOC)

: No data available.

Mobility

PBT/vPvB data

: No data available.
: P: No data available.
B: No data available.
T: No data available.

Other adverse effects

: No known significant effects or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions, and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be

considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORT INFORMATION

	Transportation - road - SANS 10228:2012	Transportation- Maritime - IMO/ IMDG	Transportation- Air – IATA
UN number	1263	1263	1263
UN proper shipping name	Paint	Paint	Paint
Transport hazard class(es)	3 	3 	3 
Packing group	II	II	II
Environmental Hazards	Environmentally hazardous	Marine pollutant	Environmentally hazardous
Additional information	No data available	Emergency schedules (EmS) F-E, S-E	Passenger and Cargo Aircraft Ltd QTY: Quantity limitation: 10 L Packaging instructions: Y344 Cargo Aircraft Only: Quantity limitation: 220 L Packaging instructions: 366 Limited Quantities – Passenger Aircraft Quantity limitation: 60L Packaging instructions: 355
Transport in bulk according to Annex II of MARPOL	No data available	No data available	No data available



STEELTECT 1400 SB

(SNK RANGE)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 11.0

73/78 and the IBC code			
------------------------	--	--	--

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product

: Relevant information regarding authorization: Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances. Relevant information regarding restrictions: None known. EU regulations: Regulation EC 1272/2008 [EU-GHS/CLP] and EU directives 67/548/EEC or EC 1999/45/EC Other National regulations: None. Standards used for PPE recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166 European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

SECTION 16: OTHER INFORMATION

History

Date of review : 30/08/2022

Date of review	Version	Amendments
30/08/2022	11.0	GHS Purple Book version 9 alignment
22/09/2020	10.0	GHS compliant
08/08/2019	9.0	-

Date of previous issue : 22/09/2020

Key to abbreviations

: ATE = Acute Toxicity Estimate
BCP Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention



STEELTECT 1400 SB

(SNK RANGE)

UN1263 PAINT

Safety Data Sheet

Date of Issue: 30/08/2022 Revision Date 30/08/2022 | Version 11.0

of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OHSA = Occupational Health and Safety Act, 1993 (South Africa)

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

UN = United Nations

References : Supplier Safety Data Sheets.

Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to readers:

Employers should use this information only as a supplement to other information gathered by them and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.