Technical Data Sheet

Date of Issue: 30/09/2022 Revision Date 30/09/2022 | Version 1.0



Product name

ACRYLINE PRE-CLEANER SB

(ATH 310)

PRODUCT DESCRIPTION

A blend or organic solvents for cleaning.

INTENDED USES

- It is degreaser for the effective and efficient removal of oil, grease, wax, from surfaces to be painted.
- General degreaser and cleaner for steel surfaces in the surface preparation process.

FEATURES AND BENEFITS

- Excellent general surface cleaner

PRODUCT INFORMATION

Appearance	Clear liquid
Practical spreading rate	±10.0m²/L for normal cleaning purposes. The actual spreading rate depends on the condition and porosity of the surface to be cleaned.
Flash Point	>23°C(typical)

APPLICATION DETAILS

Mixing	Stir with a flat paddle until completely homogeneous
Method	Spray application

STORAGE AND PACKAGING

Store away from direct sun, heat, open flames, sparks and severe cold.
Shelf Life: 36 months
Single Pack: 5L

APPLICATION INFORMATION

- Spray onto the soiled surface using spray gun and work the solution well into the surface.
- Allow approximately 15 minutes for the active solvents to penetrate and soften the deposits and then wipe off with clean cloths
- Heavy deposits and deeply penetrated oil stains may require repeated applications.
- Flammable - Do not apply to hot surfaces.
- After use always ensure that all traces are removed.

SAFETY PRECAUTIONS

- Always keep paint out of reach of children.
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.
- Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Do not smoke while painting.
- Flammable. Store in a cool dry place away from heat and sparks.
- Refer to Safety Data Sheet for complete information.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be dependable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.
NB: TO ORDER: Quote product name, product code number, packaging, and colour.

KANSAI PLASCON (PTY) LTD
10 Frederick Cooper Drive,
Factoria, Krugersdorp
South Africa
1739.
Tel: +27 11 951 4500
Fax: +27 800 110 932

PLASCON ADVISORY SERVICE: 0860 20 40 60
EMAIL: advice@kansaiplascon.co.za